CHEFALARM® THERMOMETER & TIMER

- Interchangeable NTC thermistor probes
- Programmable high/low alarm

The ChefAlarm is a professional cooking thermometer and timer which displays the countdown/up time, current temperature and simultaneously displays both the high/low alarms and max/min temperatures.

The timer is fully programmable, allowing the user to set the countdown/up time to/from 99 hours and 59 minutes. The unit incorporates a large, easy to read LCD display with user selectable backlight and a loud audible alarm with adjustable volume to 92dB.

The ChefAlarm also includes a calibration function allowing the user to fine-tune the accuracy of the thermometer (±2.2 °C). The unit is housed in a water resistant casing and is designed to either sit on a worktop or attach to an appliance using the magnetic pads at the rear of the instrument.

Available in three colours, each unit is supplied in a zip wallet complete with a penetration probe (810-071) and probe holder clip. See opposite page for full probe specification.

| Order code | Description |
|------------|-------------------|
| 810-041 | ChefAlarm - white |
| 810-044 | ChefAlarm - red |
| 810-045 | ChefAlarm - blue |



| Specification | ChefAlarm |
|----------------|-------------------------------|
| Range | -50 to 300 °C |
| Resolution | 0.1 °C/°F |
| Accuracy | ±1 °C (-20 to 120 °C) |
| Battery & life | 2 x 1.5 volt AAA - 5000 hours |
| Alarm volume | <92dB |
| Sensor type | Thermistor |
| Display | Custom LCD |
| Dimensions | 19 x 70 x 152 mm |
| Weight | 165 grams |

DISHTEMP® DISHWASHER THERMOMETER

- Simulates maximum plate surface temperatures
- FREE traceable certificate of calibration

The DishTemp thermometer simulates a plate as it's cleaned and sanitised in a commercial dishwasher, accurately recording the maximum surface temperature at the touch of a single button, eliminating the need for costly and inaccurate test strips and stem thermometers that do not stay in place or record the surface temperature of a plate.

The instrument indicates temperature over the range of 0 to 90 °C with a resolution of 0.1 °C/°F and an accuracy of ± 0.5 °C. Incorporating a durable water-tight seal, the DishTemp thermometer is waterproof to IP66 and is supplied complete with a FREE traceable certificate of calibration.

| Order code | Description |
|------------|------------------------------|
| 810-280 | DishTemp thermometer |
| 832-280 | Stainless steel wall bracket |



IP66

| Specification | DishTemp | |
|--|---------------------------------|--|
| Range | 0 to 90 °C | |
| Resolution | 0.1 °C/°F | |
| Accuracy | ±0.5 °C | |
| Battery | 3 volt CR2032 lithium coin cell | |
| Battery life | 5000 hours | |
| Display | Custom LCD | |
| Dimensions | 14 x Ø127 mm | |
| Weight | 120 grams | |
| FREE traceable certificate of calibration included | | |

